



Sales Bulletin

BRON V75-1EXC Introduction

Date: October 6, 2023

The BRON V75-1EXC is an Excavator mounted vibratory plow designed for specific sized excavator classes. The V75-1EXC fits most makes & models in the 20-25t Excavator class. Quick attachment with a hydraulic pin grabber coupler. The V75-1EXC has the capability of plowing depths up to 54” depending on ground conditions. Additional sizes available & in development.





Sales Bulletin

BRON V75-1EXC Features

BRON
POWER TO PERFORM

V75-1 EXC

VIBRATORY UTILITY PLOW

ADAPTER
Adapters with 80mm pins standard. Custom adapters available for most major makes & models upon request

OVERSIZE PINS
Oversize pins create a secure connection and can be easily removed to allow the blade to pivot for ease of transport

BLADE & CUTTING EDGES
Heat treated, wear resistant blades are available with standard 2.5" replaceable cutting edges with other widths available upon request

CHUTES
Standard and custom chutes available in various widths to match the plow to installation requirements. Adjustable height warning tape feed tubes available.

CYLINDERS
Custom engineered heavy duty cylinders allow for hydraulic lift up 22 degrees per side, and hydraulic swing up to 45 degrees per side

PINS & BUSHINGS
Robust and proven pin & bushing connections allow for smooth movement and long component life

INTEGRAL SHAKER
Reduces the required plowing power and increases productivity with a smaller carrier. Shakers help to keep soil disturbance to a minimum

FOR 20-25 TON EXCAVATORS



Sales Bulletin

Features & Benefits

Features & Benefits of the V75-1 EXC

ADAPTER

Adapters with 80mm pins standard. Custom adapters available for most major makes & models upon request

OVERSIZE PINS

Oversize pins create a secure connection and can be easily removed to allow the blade to pivot for ease of transport

BLADE & CUTTING EDGES

Heat treated, wear resistant blades are available with standard 2.5" replaceable cutting edges with other widths available upon request

CHUTES

Standard and custom chutes available in various widths to match the plow to installation requirements. Adjustable height warning tape feed tubes available

CYLINDERS

Custom engineered heavy-duty cylinders allow for hydraulic tilt up 22 degrees per side, and hydraulic swing up to 45 degrees per side

PINS & BUSHINGS

Robust and proven pin & bushing connections allow for smooth movement and long component life

INTEGRAL SHAKER

Reduces the required plowing power and increases productivity with a smaller carrier. Shakers help to keep soil disturbance to a minimum